

# STINGER®

## BULLHEAD SAFETY® EYE PROTECTION

### BH691AF

**BH6G**

Optional flame resistant foam gasket for Stinger® styles

**BH6FBG**

Optional flame resistant foam brow gasket for Stinger® styles

**LENS** **Clear Anti-Fog**

**FRAME** **Shiny Pearl Gray**

## DESCRIPTION

The rugged design of the Stinger® features rigid TPR flared temple ends, soft nose pieces, and properly placed ventilation ports to reduce fogging. With a single 9 base curve lens, it is designed for maximum impact resistance and superior side coverage.

BH6G - Optional flame-resistant foam gasket for all Stinger® styles.

BH6FBG - Optional flame resistant foam brow gasket for all Stinger® styles

## FEATURES

- AF - Anti-Fog lens: FSI brand hydrophobic anti-fog lens treatment greatly reduces fog in hot, humid, and variable temperature environments
- Rugged design for maximum resistance
- 9 base curve for superior side coverage
- Rigid, flared TPR temple ends for a secure fit
- Soft TPR nose pieces prevent slippage
- Meets ANSI/ISEA Z87.1-2020 standards

## SPECIFICATIONS

LENS	LIGHT TRANSMITTANCE	FRAME TYPE	FRAME COLOR	WEIGHT	BASE CURVE	FRAME WIDTH	TEMPLE LENGTH	END OF TIPS WIDTH
Clear Anti-Fog	89%	Vented Half Frame	Shiny Pearl Gray	30 Grams	9	142 mm	120 mm	90 mm

## PACKAGING

	EACH	INNER PACK	CASE
QUANTITY	1	12/box	12 boxes/case
UPC/GTIN	810292021481	10810292021488	20810292021485

13915 Radium St NW  
Ramsey, MN 55303

763-450-0110  
Sales@BullheadSafety.com

BullheadSafety.com

## TECHNOLOGY

All Bullhead Safety® Eyewear is made from 100% virgin materials. This style features lenses and frames constructed with the highest quality polycarbonate.



MEETS ANSI/ISEA  
Z87.1-2020  
STANDARDS



HYDROPHOBIC  
TREATMENT  
REDUCES FOG



ARC FLASH  
TESTED TO  
35 CAL/CM²



MEETS MILITARY  
SPECS FOR  
BALLISTICS



ERGONOMIC FIT  
RELIEVES  
PRESSURE



ANTI-SCRATCH  
HARD COAT  
TREATED LENS



TAPERED LENS  
ELIMINATES  
DISTORTION



FILTERS 99.9%  
UVA/UVB/UV-C  
LIGHT RAYS



PROVIDES SEAL  
AGAINST DEBRIS  
AND IMPACT  
\*Optional

